



GARLWAY MACHINERY

Concrete Mixer

GARLWAY MACHINERY

> > >

2014

10

60,000

3

300

2,000

Garl way

Machinery



: J Z C 7 5 0



1

	1.8 - 2.2 m ³ / h
	B V I S O
	1
	2

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

	J D C 3 5 0
	J D C

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0		4 5 #		
J Z C 3 5 0		4 5 #		
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		
J Z C 7 5 0		4 5 #		
J Z C 1 0 0 0		4 5 #		
J Z C 1 5 0 0		4 5 #		

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance for construction sites, road factories. Features 1600L feeding discharge, and precise mixing efficiency today!

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m ³ / h
Mixing Drum Speed	13r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

J s 3 0 0 0

: J S 3 0 0 0



J S 3 0 0 0

J S 3 0 0 0

:

	6 0 0 m

--	--

	3 1

/

--	--

--	--

: J W 4 0 0 0



	5.3	4
	37 kW	
	2.6	3.2

J d y 3 5 0

: J D Y 3 5 0



	1 18 - 21

: JZC300



Portable cement mixer for construction and DIY. High performance, easy to use, and durable design.

Parameter	Specification
Capacity	Feeding: 480L, Discharging: 300L
Productivity	9-12 m ³ /h
Motor Power	Mixing: 4KW, Lifting: 4KW, Pump: 0.55KW
Stirring Drum Speed	17 r/min
Maximum Aggregate Size	60 mm
Overall Dimension	2376 x 1990 x 2750 mm
Overall Weight	1650 kg

Application Field	Description
General Construction	Concrete mixing for civil and commercial buildings, rural self-built houses, etc.
Road and Bridge Project	Concrete mixing for road laying, bridge construction, road base, bridge pier, etc.
Concrete Component Factory	Production of small concrete components like blocks and precast panels

Product Selling Point	Description
Performance	Self-falling double-cone reversing discharging, homogeneous concrete in 35-45s
Structure	Tires and towing frame for easy transfer, adjustable height legs for stability
Operation	Water supply system with motor, pump, regulating valve, and time relay control
Quality	Designed and manufactured according to GB/T9142-2000 standard, efficient, high quality

J z c 5 0 0

: J Z C 5 0 0



J Z C 5 0 0

	J Z C 5 0 0
	5 0 0 L
	8 0 0 L
	1 8 ~ 2 0 m ³ / h
	6 0 mm
	1 3 r / mi n
	2 0 k m / h
	7 . 5 k w
	5 . 5 K W
	0 . 5 5 k w
	2 4 0 0 k g
x x	3 5 0 0 x 2 2 0 0 x 3 2 0 0 mm

: J Z C 3 5 0



J Z C 3 5 0

J Z C 3 5 0	

J s 1 0 0 0

: J S 1 0 0 0



J S 1 0 0 0

	J S 1 0 0 0
	1

J s 2 0 0 0

H

F r e i g h t

: J S 2 0 0 0



B e l l e

	J S 2 0 0 0
	2

J s 1 5 0 0

: J S 1 5 0 0



J S 1 5 0 0

	J S 1 5 0 0
	1 . 5

： JS750



	750L
	1200L
	30 - 35 m ³ / h
	30 kW 7.5 kW
	80 mm
	1.6 m / 2.7 m / 3.8 m

Hz s 50

: HZ S 50



	50	30 35
	J S 1000	
	2 × 18.5 KW	
	1000 L	
	1500 L	
	72 S	
	PLD1600	
	3.5 × 3	
	1600 L	
	3	
	80 mm	
	0 600 kg ± 1	
	0 300 kg ± 1	
	2.58 m	
	2.7 m 3.8 m	
	85.0 KW	
2.7 m	10867 mm × 4070 mm × 6560 mm	
3.8 m	17012 mm × 4070 mm × 8400 mm	
2.7 m	14870 kg	
3.8 m	17570 kg	

H z s 1 2 0

: H Z S 1 2 0



H Z S 1 2 0

	1 2 0 /
	J S 2 0 0 0
	2 × 3 7 k W
	3 2 0 0
	2
	P L D 3 2 0 0
	3 2 0 0
	2 4
	2 0
	1 2 0 m m
	± 1 %
	± 2 %
	2 × 2 0 0
	3 . 8 4 . 2
	1 4 5 - 2 0 9 . 5 k W
	9 0 × 1 0 ³ k g

	1 2 0 /

	PLC

--	--

Hz s 90

Mu l t i q u i p

: H Z S 9 0



Z S 9 0

H

	90	/	
	J S 1 5 0 0	2 × 3 0 k W	1 5 0 0 L 6 0 S
	P L D 2 4 0 0	2 4 0 0 L	4
	8 0 m m		
-	(0 - 9 0 0) ± 1 % k g		
-	(0 - 5 0) ± 1 % k g		
-	0 - 5 0 0 0 ± 2 % k g		
	3 × 1 0 0 t		
	3 . 8	4 . 2	
	1 6 4 k W		
	2 4	× 1 0	× 1 8
	6 5 0 0 0 k g		
	90		
	J S 1 5 0 0		

H z s 1 8 0

: H Z S 1 8 0



	1 8 0
	J S 3 0 0 0 M A 0 4 5 0 0 / 3 0 0 0 S D S H O
	1 1 0 k W 2 × 5 5 k W
	3
	P L D 4 8 0 0
	4 8 0 0 L
	4 6
	0 1 5 0 0 k g ± 1
	0 - 5 0 k g (± 1 %)
	4
	2 0 0
	1 8 0
	J S 3 0 0 0

P L C

--	--

H z s 7 5

: H Z S 7 5



H Z S 7 5

	75	/		
	J S 1 5 0 0		3 0 × 2 k W	1 . 5
	2 . 4			
	P L D 2 4 0 0	4	2 4 0 0 L	8 0 m m
	± 2		± 1	
	3 . 8			
	2 4 3 5 0 m m x 1 0 5 9 5 m m x 1 8 7 0 4 m m			
	1 2 0 k W			
	6 0			

	75	/		
	J S 1 5 0 0			

Hz s 3 5

: H Z S 3 5



	3 5	2 5 3 5
	J S 7 5 0	
	3 0 K W	
	1 2 0 0 L	
	0 . 7 5	
	7 5 S	
	P L D 1 2 0 0 3	
	3 6	
	1 2 0 0 L	
	3	
	6 0 m m	8 0 m m
	0 2 5 0 k g	1 k g
	0 - 2 0 0 k g	1 k g
	2 . 8 2 m	
	3 . 8 m	
	7 4 . 9 K W	
	4 9 5 1 m m × 3 6 5 0 m m × 6 2 2 5 m m	

	J S 7 5 0

	5 0 , 0 0 0
--	-------------

--	--

Hz s 25

: HZ S 25



	25 / 20 /
	JS500
	50.25KW
	72S
	0.5
	0.75
	PLD800 PLD1200 3
	3.5
	800L 1200L
	50mm
	±2 ±1
	1.5-3.8m
	50.25KW
	11693mm × 13060mm × 17245mm
	17500kg

	JS500
	/



Garl way Machinery

55

