



G A R L W A Y M A C H I N E R Y

GARLWAY MACHINERY

> > >

2014

10

60,000

3

300

2,000

Garl way

Machinery



: J W5 0 0 0



	5			
	30 k W			
	485	500		
	2.6	3.2	-3.2	
-	30 k W			
-		30	4	
-				
-				
-				

: G J W 3 5 0



	3 5 0 L
	2 1 r /
	5 . 5 k W
	1 2 0 0 × 1 4 0 0 m m
	3 5 0 k g

J w1 0 0 0

: J W1 0 0 0



	1 0 0 0 L 1 2 0 0 - 1 4 0 0 L
	4 5 r / mi n
	1 5 k w
	1 6 0 0 × 2 0 0 0 mm 1 8 0 0 × 1 6 0 0 mm
	6 5 0 k g

: J W 3 0 0 0



	3
	18.5 kW
	35
	30 rpm
	2200 mm x 2200 mm x 1600 mm
	850 kg

Hz s 3 5

: HZ S 3 5



	3 5 2 5 3 5
	J S 7 5 0
	3 0 K W
	1 2 0 0 L
	0 . 7 5
	7 5 S
	PL D 1 2 0 0 3
	3 6
	1 2 0 0 L
	3
	6 0 mm 8 0 mm
	0 2 5 0 k g 1 k g
	0 - 2 0 0 k g 1 k g
	2 . 8 2 m
	3 . 8 m
	7 4 . 9 K W
	4 9 5 1 mm × 3 6 5 0 mm × 6 2 2 5 mm

	J S 7 5 0

	5 0 , 0 0 0
--	-------------

--	--

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0		4 5 #		
J Z C 3 5 0		4 5 #		
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		
J Z C 7 5 0		4 5 #		
J Z C 1 0 0 0		4 5 #		
J Z C 1 5 0 0		4 5 #		

: J W5 0 0



3 5 r p m

5 0 0 L
7 . 5 K W

	5 0 0 L
	3 5 r p m
	7 . 5 K W
	1 5 0 0 m m × 1 4 0 0 m m

H z s 1 2 0

: H Z S 1 2 0



H Z S 1 2 0

	1 2 0 /
	J S 2 0 0 0
	2 × 3 7 k W
	3 2 0 0
	2
	P L D 3 2 0 0
	3 2 0 0
	2 4
	2 0
	1 2 0 m m
	± 1 %
	± 2 %
	2 × 2 0 0
	3 . 8 4 . 2
	1 4 5 - 2 0 9 . 5 k W
	9 0 × 1 0 ³ k g

	1 2 0 /

	PLC

--	--

: J W 4 0 0



5 K W 1 9 r p m 4 0 0 L 5 .

	4 0 0 L
	1 9 r p m
	5 . 5 K W
	1 2 0 0 m m × 1 2 0 0 m m
	1 . 2
	/

: J W6 0 0 0



3 7 k W

6 m³

	6		
	3 7 k W		
	4 1 0 5 4		
	4 8 5	5 0 0	
	2 . 8	1	
	3	2	1 8 0 °

Hz s 90

Mu l t i q u i p

: H Z S 9 0



Z S 9 0

H

	90	/		
	J S 1 5 0 0		2 × 3 0 k W	1 5 0 0 L
	6 0 S			
	P L D 2 4 0 0	2 4 0 0 L	4	
	8 0 m m			
-	(0 - 9 0 0) ± 1 % k g			
-	(0 - 5 0) ± 1 % k g			
-	0 - 5 0 0 0 ± 2 % k g			
	3 × 1 0 0 t			
	3 . 8	4 . 2		
	1 6 4 k W			
	2 4	× 1 0	× 1 8	
	6 5 0 0 0 k g			
	9 0			
	J S 1 5 0 0			

: J W1 5 0 0



3 6 0 °

	1 . 5	
	1 . 8	6 0
	1 5 k W	
	3 6 0	

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance for construction sites, road factories. Features 1600L feeding discharge, and precise mixing efficiency today!

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m ³ / h
Mixing Drum Speed	13r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

: JW2000



	2000L
	45r /
	22kW
	2800mm × 2800mm × 2000mm
	1200kg
	2 70

： J W 7 5 0



	750L
	1200L
	30 - 35 m ³ / h
	80 mm
	2 × 7.5 kW
	7.5 kW
	1.1 kW
	20 r / mi n
	2650 mm × 1315 mm × 2180 mm
	1.2

Hz s 25

: HZ S 25



	25 / 20 /
	JS500
	50.25KW
	72S
	0.5
	0.75
	PLD800 PLD1200 3
	3.5
	800L 1200L
	50mm
	± 2 ± 1
	1.5 - 3.8m
	50.25KW
	11693mm × 13060mm × 17245mm
	17500kg

	JS500
	/

: J Z C 7 5 0



1

	1.8 - 2.2 m ³ / h
	B V I S O
	1
	2

H z s 1 8 0

: H Z S 1 8 0



	1 8 0
	J S 3 0 0 0 M A 0 4 5 0 0 / 3 0 0 0 S D S H O
	1 1 0 k W 2 × 5 5 k W
	3
	P L D 4 8 0 0
	4 8 0 0 L
	4 6
	0 1 5 0 0 k g ± 1
	0 - 5 0 k g (± 1 %)
	4
	2 0 0
	1 8 0
	J S 3 0 0 0

P L C

--	--

H z s 7 5

: H Z S 7 5



H Z S 7 5

	75	/			
	J S 1 5 0 0		3 0 × 2 k W	1 . 5	2 . 4
	P L D 2 4 0 0	4	2 4 0 0 L	8 0 m m	
	± 2		± 1		
	3 . 8				
	2 4 3 5 0 m m x 1 0 5 9 5 m m x 1 8 7 0 4 m m				
	1 2 0 k W				
	6 0				

	75	/			
	J S 1 5 0 0				

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

	J D C 3 5 0
	J D C

Hz s 50

: HZ S 50



	50	30 35
	J S 1000	
	2 × 18.5 KW	
	1000 L	
	1500 L	
	72 S	
	PLD1600	
	3.5 × 3	
	1600 L	
	3	
	80 mm	
	0 600 kg ± 1	
	0 300 kg ± 1	
	2.58 m	
	2.7 m 3.8 m	
	85.0 KW	
2.7 m	10867 mm × 4070 mm × 6560 mm	
3.8 m	17012 mm × 4070 mm × 8400 mm	
2.7 m	14870 kg	
3.8 m	17570 kg	

	50 /
	JS1000



Garl way Machinery

55

