



GARLWAY MACHINERY

,

,

,

GARLWAY MACHINERY

> > >

2014

10

60,000

3

300

2,000

Garlway
Machinery



: JW5000



	5
	30 kW
	485500
	2.63.2~3.2
-	30 kW
-	304
-	
-	
-	

: JZC300



Portable cement mixer for construction and DIY. High performance, durable design.

Parameter	Specification
Capacity	Feeding: 480L, Discharging: 300L
Productivity	9-12 m ³ /h
Motor Power	Mixing: 4KW, Lifting: 4KW, Pump: 0.55KW
Stirring Drum Speed	17 r/min
Maximum Aggregate Size	60 mm
Overall Dimension	2376 × 1990 × 2750 mm
Overall Weight	1650 kg

Application Field	Description
General Construction	Concrete mixing for civil and commercial buildings, rural self-built houses, Road and Bridge Project
Concrete Component Factory	Concrete mixing for road laying, bridge construction, road base, bridge pier
	Production of small concrete components like blocks and precast panels

Product Selling Point	Description
Performance	Self-falling double-cone reversing discharging, homogeneous concrete in 35-40s
Structure	Tires and towing frame for easy transfer, adjustable height legs for stability
Operation	Water supply system with motor, pump, regulating valve, and time relay control
Quality	Designed and manufactured according to GB/T9142-2000 standard, efficient, high

J z c 5 0 0

: J Z C 5 0 0



J Z C 5 0 0

	J Z C 5 0 0
	5 0 0 L
	8 0 0 L
	1 8 ~ 2 0 m ³ / h
	6 0 mm
	1 3 r / m i n
	2 0 k m / h
	7 . 5 k w
	5 . 5 K W
	0 . 5 5 k w
	2 4 0 0 k g
x x	3 5 0 0 x 2 2 0 0 x 3 2 0 0 m m

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance for construction sites, road factories. Features 1600L feeding capacity, and precise mixing efficiency today!

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m³ / h
Mixing Drum Speed	13r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

: J Z C 7 5 0



1

	1 8 2 2m3 / h
	B V I S O
	1
	2

: JW2000



	2000L
	45r /
	22kW
	2800mm × 2800mm × 2000mm
	1200kg
2	70

: JW1500



360°

	1.5
	1.860
	15 kW
	360

: JW750



	750 L
	1200 L
	30 - 35m³ / h
	80mm
	2 × 7.5 kw
	7.5 kw
	1.1 kw
	20 r / min
	2650mm × 1315mm × 2180mm
	1.2

J w 1 0 0 0

: J W 1 0 0 0



	1 0 0 0 L 1 2 0 0 - 1 4 0 0 L
	4 5 r / m i n
	1 5 k w
	€ 1 6 0 0 × 2 0 0 0 m m € 1 8 0 0 × 1 6 0 0 m m
	6 5 0 k g

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

	J D C 3 5 0
	J D C

H z s 7 5

: H Z S 7 5



H Z S 7 5

	7 5	/		
	J S 1 5 0 0		3 0 × 2 k W	1 . 5
				2 . 4
	P L D 2 4 0 0	4	2 4 0 0 L	8 0 m m
	± 2		± 1	
	3 . 8			
	2 4 3 5 0 m m	x	1 0 5 9 5 m m	x
			1 8 7 0 4 m m	
	1 2 0 k W			
	6 0			

	7 5	/		
	J S 1 5 0 0			

H z s 2 5

: H Z S 2 5



	2 5 / 2 0 /
	J S 5 0 0
	5 0 . 2 5 K W
	7 2 S
	0 . 5
	0 . 7 5
	PLD800 PLD1200 3
	3 . 5
	8 0 0 L 1 2 0 0 L
	5 0 m m
	± 2 ± 1
	1 . 5 - 3 . 8 m
	5 0 . 2 5 K W
	1 1 6 9 3 m m × 1 3 0 6 0 m m × 1 7 2 4 5 m m
	1 7 5 0 0 k g

	JS500
	/

: J Z C 3 5 0



J Z C 3 5 0

	J Z C 3 5 0

: JW6000



37 kW

6 m³

	6		
	37 kW		
	41054		
	485	500	
	3	2.8	1
	3	2	180°

: JW3000



	3
	18.5kW
	35
	30rpm
	2200mm x 2200mm x 1600mm
	850kg

H z s 3 5

: H Z S 3 5



	3 52 5 3 5
	J S 7 5 0
	3 0 K W
	1 2 0 0 L
	0 . 7 5
	7 5 S
	P L D 1 2 0 0 3
	3 6
	1 2 0 0 L
	3
	6 0 m m8 0 m m
	0 2 5 0 k g1 k g
	0 - 2 0 0 k g1 k g
	2 . 8 2 m
	3 . 8 m
	7 4 . 9 K W
	4 9 5 1 m m × 3 6 5 0 m m × 6 2 2 5 m m

	JS 750

	50,000
--	--------

--	--

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0		4 5 #		
J Z C 3 5 0		4 5 #		
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		
J Z C 7 5 0		4 5 #		
J Z C 1 0 0 0		4 5 #		
J Z C 1 5 0 0		4 5 #		

H z s 1 2 0

: H Z S 1 2 0



H Z S 1 2 0

	1 2 0 /
	J S 2 0 0 0
	2 × 3 7 kW
	3 2 0 0
	2
	P L D 3 2 0 0
	3 2 0 0
	2 4
	2 0
	1 2 0 mm
	± 1 %
	± 2 %
	2 × 2 0 0
	3 . 8 4 . 2
	1 4 5 - 2 0 9 . 5 kW
	9 0 × 1 0 ³ kg

	1 2 0 /

--	--

P L C

--	--

Hzs90 Multiquip

: HZS90



H

ZS90

	90 /
	JS1500 2×30kW 1500L 60S
	PLD2400 2400L 4
	80mm
-	(0-900)±1%kg
-	(0-50)±1%kg
-	0-5000±2%kg
	3×100t
	3.8 4.2
	164kW
	24 ×10 ×18
	65000kg
	90
	JS1500

--	--

: JW4000



	5 . 3	4	
	3 7 kW		
	2 . 6	3 . 2	

J s 1 0 0 0

: JS1000



JS1000

	JS1000
	1

J s 2 0 0 0

F r e i g h t

: J S 2 0 0 0



B e l l e

	J S 2 0 0 0
	2

J s 1 5 0 0

: J S 1 5 0 0



J S 1 5 0 0

	J S 1 5 0 0
	1 . 5

Hzs 50

: HZS50



	50 30 35
	JS1000
	2 × 18.5KW
	1000L
	1500L
	72S
	PLD1600
	3.5 × 3
	1600L
	3
	80mm
	0 600kg ± 1
	0 300kg ± 1
	2.58m
	2.7m 3.8m
	85.0KW
2.7m	10867mm × 4070mm × 6560mm
3.8m	17012mm × 4070mm × 8400mm
2.7m	14870kg
3.8m	17570kg

: JW400



5 KW

19 rpm

400 L 5 .

	400 L
	19 rpm
	5.5 KW
	1200 mm × 1200 mm
	1.2
	/

: G J W 3 5 0



	3 5 0 L
	2 1 r /
	5 . 5 k W
	€ 1 2 0 0 × 1 4 0 0 m m
	3 5 0 k g

H z s 1 8 0

: H Z S 1 8 0



	180
	JS3000MAO4500/3000SDSHO
	110kW2×55kW
	3
	PLD4800
	4800L
	46
	01500kg±1
	0-50kg(±1%)
	4
	200
	180
	JS3000

P L C	

J d y 3 5 0

: J D Y 3 5 0



	118 - 21

J s 3 0 0 0

: J S 3 0 0 0



J S 3 0 0 0

J S 3 0 0 0

:

	6 0 0 m

--	--

	3 1

/

--	--

--	--

: JW500

500 L

35 r p m

7 . 5 KW



	500 L
	35 r p m
	7 . 5 KW
	1500 mm× 1400 mm

: JS750



	750 L
	1200 L
	30 - 35 m ³ / h
	30 kW 7.5 kW
	80 mm
	1.6 m / 2.7 m / 3.8 m



Garlway Machinery

55

